

<https://prom-nasos.pro>
<https://bts.net.ua>
<https://prom-nasos.com.ua>
+38 095 656-37-57,
+38 067 360-71-01,
+38 063 362-12-31,
info@prom-nasos.pro



Catalog CPS series centrifugal pump

<https://bts.net.ua>

Product introduction:

These pumps are single stage centrifugal pumps, suitable for both domestic and industrial applications to convey clean liquids and non-aggressive chemical fluids. The hydraulic characteristic is with higher head and smaller capacity



Component Construction:

Pump body: Stainless steel 304
 Pump support: Aluminum
 Motor Housing: Aluminum
 Impeller: Stainless Steel/PPO Plastic
 Motor Shaft: Carbon Steel(304SS if request)
 Mechanical seal: Ceramic/Graphite




Operating Condition:

Liquid Temperature up to 60°C
 Ambient Temperature up to 40°C
 Total Suction lift up to 9m

Motor:

Single Phase 220V/50Hz, 110V/60Hz if request
 Insulation Class B
 Production: IP44, IP54 if request
 Cooling: External Ventilation
 With Thermal Protector
 Continuous Work S1

PERFORMANCE CHART AT n = 2900rpm



MODEL PARAMETERS

Model	Power		Max.Flow	Max.Head	In/outlet	Max.Suct	G.W.	Dimension
	Kw	Hp	m³/h	m	inch	m	kgs	mm
CPS-18S	0.37	0.5	6.6	18	1.25"x1"	9	9	310*195*220
CPS-20S	0.55	0.75	7.8	20	1.25"x1"	9	10	330*230*245
CPS-26S	0.75	1	8.7	26	1.25"x1"	9	11	330*230*245
CPS-36S	1.1	1.5	11.4	34	1.25"x1"	9	16.5	390x250x280